

BOSCH POWER TOOLS

Drill

GBM 6 RE

NEW



Capacity

Power Input	: 350 W
In Steel	: 6.5 mm
In Aluminium	: 6 mm
In Wood	: 15 mm
No-load Speed	: 0-4,000 rpm
Weight	: 1.1 kg

GBM 10 RE

NEW



Capacity

Power Input	: 450 W
In Steel	: 10 mm
In Aluminium	: 10 mm
In Wood	: 25 mm
No-load Speed	: 0-2,600 rpm
Weight	: 1.3 kg

GBM 13 RE

NEW



Capacity

Power Input	: 600 W
In Steel	: 13 mm
In Aluminium	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0-2,600 rpm
Weight	: 1.65 kg

GBM 13-2



Capacity

Power Input	: 550 W
In Steel	: 13 / 8 mm
In Wood	: 32 / 20 mm
No-load Speed: Hi	: 1,900 rpm
Lo	: 1,000 rpm
Weight	: 1.9 kg

GBM 13 HRE "High Torque"



Capacity

Power Input	: 550 W
In Steel	: 13 mm
In Aluminium	: 20 mm
In Wood	: 40 mm
No-load Speed	: 0-550 rpm
Torque (Approx.)	: 40 Nm
Weight	: 2.1 kg

GBM 16-2 RE



Capacity

Power Input	: 900 W
In Steel	: 16 / 8 mm
In Wood	: 20 / 13 mm
No-load Speed: Hi	: 0 - 1,200 rpm
Lo	: 0 - 520 rpm
Weight	: 3.7 kg

GBM 23-2 E

NEW



Capacity

Power Input	: 1,150 W
In Steel	: 23 / 13 mm
In Wood	: 50 / 35 mm
No-load Speed: Hi	: 0 - 640 rpm
Lo	: 0 - 280 rpm
Weight	: 4.6 kg

Impact Drill

GSB 10 RE



Capacity

Power Input	: 500 W
In Masonry	: 10 mm
In Steel	: 8 mm
In Wood	: 20 mm
No-load Speed	: 0-2,600 rpm
Weight	: 1.5 kg

GSB 13 RE



Capacity

Power Input	: 600 W
In Masonry	: 13 mm
In Steel	: 10 mm
In Wood	: 25 mm
No-load Speed	: 0-2,800 rpm
Weight	: 1.65 kg

GSB 16 RE



Capacity

Power Input	: 701 W
In Masonry	: 16 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0-3,000 rpm
Weight	: 1.9 kg

GSB 20-2 / GSB 20-2 RE*



Capacity

Power Input	: 701 W
In Concrete	: 20 / 13 mm
In Steel	: 13 / 8 mm
In Wood	: 40 / 25 mm
No-load Speed	
GSB 20-2	: 1000 / 3000 rpm
GSB 20-2 RE	: 0-1000 / 3000 rpm
No-load Impact Rate	
GSB 20-2	: 16000 / 48000 bpm
GSB 20-2 RE	: 0-16000 / 48000 bpm
Weight GSB 20-2	: 1.7 kg
GSB 20-2 RE	: 2.2 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Cordless Drill / Screwdriver

IXO II 3.6 V-Li



Capacity

Max. Screw Dia.	: 5 mm
Max. Torque	: 4 Nm
No-load Speed	: 0 - 180 rpm
Battery Voltage	: 3.6 V / 1.3 Ah
Weight	: 0.3 kg

GSR ProDrive (3.6 V)

NEW



Capacity

Max. Screw Dia.	: 5 mm
Max. Torque	: 7 Nm
No-load Speed	: 0-250 rpm
Battery Voltage	: 3.6 V / 1.3 Ah
Weight	: 0.5 kg

GSR 10.8 V-Li-2

NEW



Capacity

Drilling Dia.: In Steel	: 10 mm
In Wood	: 19 mm
Max. Torque	: 30 Nm
No-load Speed	: 0-400 / 1,100 rpm
Battery Voltage	: 10.8 V / 1.3 Ah
Weight	: 1.1 kg

GSR 7.2-2



Capacity

Drilling Dia.: In Steel	: 10 mm
In Wood	: 17 mm
Max. Torque	: 21 Nm
Max. Screw Dia.	: 6 mm
No-load Speed	: 0-400 / 1,000 rpm
Battery Voltage	: 7.2 V / 1.5 Ah
Weight	: 1.4 kg

GSR 9.6-2



Capacity

Drilling Dia.: In Steel	: 10 mm
In Wood	: 20 mm
Max. Torque	: 25 Nm
Max. Screw Dia.	: 6 mm
No-load Speed	: 0-400 / 1,000 rpm
Battery Voltage	: 9.6 V / 1.5 Ah
Weight	: 1.5 kg


GSR 12-2



Capacity

Drilling Dia.: In Steel	: 10 mm
In Wood	: 23 mm
Max. Torque	: 27 Nm
Max. Screw Dia.	: Up to 7 mm
No-load Speed	: 0-400 / 1,200 rpm
Battery Voltage	: 12 V / 1.5 Ah
Weight	: 1.6 kg

GSR 14.4-2



Capacity

Drilling Dia.: In Steel	: 10 mm
In Wood	: 26 mm
Max. Torque	: 30 Nm
Max. Screw Dia.	: 8 mm
No-load Speed	: 0-400 / 1,400 rpm
Battery Voltage	: 14.4 V / 1.5 Ah
Weight	: 1.7 kg

Cordless Impact Drill / Cordless Impact Wrench

GSB 14.4 VE-2-Li

NEW



Capacity

Clutch Settings	: 25+drilling
Max. Torque	: 80 Nm
No-load Speed	: 0-380 / 0-1,700 rpm
Battery Voltage	: 14.4 V / 2.6 Ah
Weight	: 2.3 kg

GDS 12 V



Capacity

Toolholder	: 1/2" external square
No-load Speed	: 0-2,800 rpm
Impact Rate	: 3,200 bpm
Max. Torque	: 175 Nm
Battery Voltage	: 12 V / 2.6 Ah
Weight	: 1.8 kg

GDS 14.4 V-Li

NEW



Capacity

Toolholder	: 1/2" external square
No-load Speed	: 0-2,800 rpm
Impact Rate	: 3,200 bpm
Max. Torque	: 160 Nm
Battery Voltage	: 14.4 V / 2.6 Ah
Weight	: 1.6 kg

GDS 18 V-Li

NEW



Capacity

Toolholder	: 1/2" external square
No-load Speed	: 0-2,800 rpm
Impact Rate	: 0-3,200 bpm
Max. Torque	: 170 Nm
Battery Voltage	: 18 V / 2.6 Ah
Weight	: 1.7 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Cordless Angle Driver

GW1 10.8 V-Li



Capacity	
Drilling Dia. :	In Steel : 8 mm
	In Wood : 10 mm
Max. Torque :	13 Nm
Max. Screw Dia. :	5 mm
No-load Speed :	0-585 rpm
Battery Voltage :	10.8 V / 1.3 Ah
Weight :	1.1 kg

Cordless Impact Driver

GDR 10.8 V-Li



Capacity	
Toolholder System :	1/4" Hex (6.35 mm)
No-load Speed :	0-1,800 rpm
Impact Rate :	0-3,000 bpm
Max. Torque :	100 Nm
Battery Voltage :	10.8 V / 1.3 Ah
Weight :	1.0 kg

GDR 12 V



Capacity	
Toolholder System :	1/4" Hex (6.35 mm)
No-load Speed :	0-2,800 rpm
Impact Rate :	0-3,200 bpm
Max. Torque :	125 Nm
Battery Voltage :	12 V / 2.0 Ah
Weight :	1.8 kg

GDR 14.4 V-Li



Capacity	
Toolholder System :	1/4" Hex (6.35 mm)
No-load Speed :	0-2,800 rpm
Impact Rate :	0-3,200 bpm
Max. Torque :	150 Nm
Battery Voltage :	14.4 V / 2.6 Ah
Weight :	1.6 kg

Cordless Multi-Cutter

GDR 18 V-Li



Capacity	
Toolholder System :	1/4" Hex (6.35 mm)
No-load Speed :	0-2,800 rpm
Impact Rate :	0-3,200 bpm
Max. Torque :	170 Nm
Battery Voltage :	18 V / 2.6 Ah
Weight :	1.7 kg

GOP 10.8 V-Li



Capacity	
Oscillation angle on left / right :	1.4°
No-load Speed :	5,000 - 20,000 rpm
Battery Voltage :	10.8 V / 1.3 Ah
Weight :	1.0 kg

GBH 36 V-Li



Capacity	
In Concrete :	26 mm
In Steel :	13 mm
In Wood :	30 mm
Rated Speed :	0-960 rpm
Impact Rate :	0-4,260 bpm
Battery Voltage :	36 V / 2.0 Ah
Weight :	4.3 kg

GBH 36 V-Li Compact



Capacity	
In Concrete :	4-18 mm
In Steel :	13 mm
In Wood :	30 mm
Rated Speed :	0-1,500 rpm
Impact Rate :	0-4,850 bpm
Battery Voltage :	36 V / 1.3 Ah
Weight :	2.9 kg

Rotary Hammer with SDS-Plus

GBH 2-18 RE



Capacity	
Power Input :	550 W
In Concrete :	18 mm
In Steel :	13 mm
In Wood :	30 mm
No-load Speed :	450-1,550 rpm
Impact Rate :	0-3,960 bpm
Weight :	2.0 kg

GBH 2-22 E / GBH 2-22 RE *



Capacity	
Power Input :	620 W
In Concrete :	22 mm
In Steel :	13 mm
In Wood :	30 mm
No-load Speed :	0-1,000 rpm
Impact Rate :	0-4,400 bpm
Weight :	2.3 kg

GBH 2-26 E / GBH 2-26 RE *



Capacity	
Power Input :	800 W
In Concrete :	4-26 mm
In Steel :	Up to 13 mm
In Wood :	Up to 30 mm
No-load Speed :	0-900 rpm
Impact Rate :	0-4,400 bpm
Weight :	2.7 kg

GBH 2-26 DFR



Capacity	
Power Input :	800 W
In Concrete :	4 - 26 mm
In Steel :	Up to 13 mm
In Wood :	Up to 30 mm
No-load Speed :	0 - 900 rpm
Impact Rate :	0 - 4,000 bpm
Weight :	2.9 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

GBH 2-23 REA



Capacity

Power Input	: 710 W
In Concrete	: 4 - 23 mm
In Steel	: Up to 13 mm
In Wood	: Up to 30 mm
No-load Speed	: 0 - 1,000 rpm
Impact Rate	: 0 - 4,400 bpm
Weight	: 2.9 / 3.6 kg


GBH 3-28 E



Capacity

Power Input	: 720 W
Max. Bit Diameter	: 28 mm
Max. Core Bit Diameter	: 80 mm
No-load Speed	: 0 - 800 rpm
Impact Rate	: 0 - 4,000 bpm
Impact Force	: 0 - 3.3 J
Weight	: 3.3 kg


GBH 3-28 DFR



Capacity

Power Input	: 800 W
In Concrete	: 28 mm
In Steel	: Up to 13 mm
In Wood	: Up to 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,000 bpm
Weight	: 3.6 kg

GBH 4-32 DFR



Capacity

Power Input	: 900 W
In Concrete	: 32 mm
In Steel	: Up to 13 mm
In Wood	: Up to 32 mm
No-load Speed	: 0 - 760 rpm
Impact Rate	: 0 - 3,600 bpm
Weight	: 4.7 kg

Ratary Hammer with SDS-Max

GBH 5-38 D



Capacity

Power Input	: 1,050 W
Max. Bit Diameter	: 38 mm
Max. Core Bit Diameter	: 90 mm
No-load Speed	: 320 rpm
Impact Rate	: 0 - 2,900 bpm
Weight	: 5.8 kg

GBH 7-46 DE



Capacity

Power Input	: 1,350 W
Max. Bit Diameter	: 45 mm
Max. Core Bit Diameter	: 150 mm
No-load Speed	: 145 - 280 rpm
Impact Rate	: 1,375 - 2,800 bpm
Impact Force	: 2 - 15 J
Weight	: 8.2 kg

Demolition Hammer

GSH 3 E



Capacity

Power Input	: 650 W
Impact Rate	: 0 - 3,500 bpm
Impact Force	: 4.3 J
Weight	: 3.5 kg

GSH 388 / GSH 388 X*



Capacity

Power Input	: 1,050 W
Impact Rate	: 2,800 bpm
Impact Force	: 8 - 10 J
Weight	: 4.9 kg

GSH 5 CE



Capacity

Power Input	: 1,150 W
Impact Rate	: 1,300 - 2,900 bpm
Impact Force	: 2 - 13 J
Weight	: 6.2 kg

GSH 11 E



Capacity

Power Input	: 1,500 W
Impact Rate	: 900 - 1,800 bpm
Impact Force	: 6 - 25 J
Weight	: 10.1 kg

GSH 16-30



Capacity

Power Input	: 1,750 W
Impact Rate	: 1,300 bpm
Impact Force	: 45 J
Weight	: 16.5 kg

GSH 27



Capacity

Power Input	: 1,900 W
Impact Rate	: 1,030 bpm
Impact Force	: 60 J
Weight	: 29 kg

Straight Grinder

GGG 27



Capacity

Power Input	: 500 W
Collet	: 6 mm
Grinding Points (Diameter): Max.	: 25 mm
No-load Speed	: 27,000 rpm
Weight	: 1.3 kg

GGG 27 L



Capacity

Power Input	: 500 W
Collet	: 6 mm
Grinding Points (Diameter): Max.	: 25 mm
No-load Speed	: 27,000 rpm
Weight	: 1.6 kg

GGG 6 S



Capacity

Power Input	: 1,200 W
Grinding Points (Diameter): Max.	: 125 mm
No-load Speed	: 6,800 rpm
Weight	: 3.9 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Angle Grinder

GWS 6-100



Capacity

Power Input	: 670 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 1.8 kg

GWS 7-100



Capacity

Power Input	: 720 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 1.8 kg

GWS 8-100 C / GWS 8-100 CE*



Capacity

Power Input	: 850 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
GWS 8-100 C	: 2,800 - 11,000 rpm
GWS 8-100 CE	: 2,800 - 11,000 rpm
Weight	: 1.8 kg

GWS 11-125 CI



Capacity

Power Input	: 1,100 W
Grinding / Cutting Disc Diameter	: 125 mm
Wire Cup Brush Diameter	: 75 mm
No-load Speed	: 11,000 rpm
Weight	: 2 kg

GWS 14-125 INOX



Capacity

Power Input	: 1,400 W
Grinding / Cutting Disc Diameter	: 125 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 2,500 - 7,500 rpm
Weight	: 2.2 kg

GWS 14-125 CI



Capacity

Power Input	: 1,400 W
Grinding / Cutting Disc Diameter	: 125 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 2.2 kg

GWS 20-180



Capacity

Power Input	: 2,000 W
Grinding / Cutting Disc Diameter	: 180 mm
Wire Cup Brush Diameter	: 100 mm
No-load Speed	: 8,500 rpm
Weight	: 4.2 kg

GWS 20-230



Capacity

Power Input	: 2,000 W
Grinding / Cutting Disc Diameter	: 230 mm
Wire Cup Brush Diameter	: 100 mm
No-load Speed	: 6,500 rpm
Weight	: 4.2 kg

Impact Wrench

GDS 18 E



Capacity

Power Input	: 500 W
Bolts KW	: M6 - M18
Torque	: 70 - 250 Nm
No-load Speed	: 500 - 1,300 rpm
Torque	: 70.0 - 250.0 Nm
Weight	: 3.3 kg

Paint Stirrer

GRW 11 E



Capacity

Power Input	: 1,150 W
No-load Speed	: 0 - 260 / 0 - 640 rpm
Tool Bolder	: 5/8"
Torque	: 105 / 50 Nm
Spindle Collar Diameter	: 43mm
Weight	: 4.2 kg

Bench Grinder

GSM 200



Capacity

Power Input	: 700 W
Grinding / Cutting Disc Diameter	: 200 mm
No-load Speed	: 2,800 rpm
Weight	: 16.2 kg

Screwdriver

GSR 6-25 TE / GSR 6-45 TE



Capacity

Power Input	: 701 W
Self-Tapping Screws	: Up to 6 mm diameter
No-load Speed	: 0 - 2,500 rpm
GSR 6-45 TE	: 0 - 4,500 rpm
Weight	: 1.4 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Shear

GSC 2.8



Capacity

Power Input	: 500 W
In Steel	: 2.8 mm
In Aluminium	: 3.5 mm
No-load Stroke Rate	: 2,400 rpm
Weight	: 2.7 kg

Nibbler

GNA 2.0



Capacity

Power Input	: 500 W
Mild Steel	: 2.0 mm
Stainless Steel	: 1.0 mm
No-load Speed	: 2,400 stroke/min
Weight	: 2.0 kg

Diamond Wheel Cutter

GDM 12-34



Capacity

Power Input	: 1,250 W
Blade Diameter	: 110 mm
Max. Cutting Depth	: 34 mm
Base Plate	: 100 x 190 mm
No-load Speed	: 13,000 rpm
Weight	: 2.8 kg

Jigsaw

GST 65 / GST 65 E *



Capacity

Power Input	: 400 W
In Wood	: 65 mm
In Steel	: 3 mm
No-load Stroke Rate	: 3,100 spm (GST 65) 500 - 3,100 spm (GST 65 E)
Weight	: 1.7 kg

GST 80 PBE



Capacity

Power Input	: 580 W
In Wood	: 85 mm
In Steel	: 10 mm
No-load Stroke Rate	: 500 - 3,100 spm
Weight	: 2.4 kg

Sabre Saw

GSA 900 E



Capacity

Power Input	: 900 W
Stroke Length	: 28 mm
No-load Stroke Rate	: 0 - 2,700 spm
Weight	: 3.4 kg

GSA 1100 E



Capacity

Power Input	: 1,100 W
Cutting depth: In Wood	: 230 mm
In Metal	: 20 mm
No-load Stroke Rate	: 0 - 2,700 spm
Weight	: 3.6 kg

Cordless Sabre Saw

GSA 1200 E



Capacity

Power Input	: 1,200 W
Stroke Length	: 19 mm / 32 mm
No-load Stroke Rate	: 0 - 2,800 spm
Weight	: 3.7 kg

GSA 1500 PCE



Capacity

Power Input	: 1,500 W
Cutting depth: in Wood	: 230 mm
in Metal	: 20 mm
No-load Stroke Rate	: 0 - 2,800 spm
Weight	: 4.3 kg

GSA 18 V-Li



Capacity

Stroke Length	: 28 mm
No-load Stroke Rate	: 0 - 2,400 / 0 - 2,700 spm
Battery Voltage	: 18 V / 2.6 Ah
Weight	: 3.4 kg

GKS 190



Capacity

Power Input	: 1,400 W
Blade Diameter	: 184 mm
Max. Cutting Capacities	
at 90°	: 68 mm
at 45°	: 48 mm
No-load Speed	: 5,500 rpm
Weight	: 4.1 kg

Cordless Circular Saw

GKS 18 V-Li



Capacity

Blade Diameter	: 165 mm
Max. Cutting Capacities	
at 90°	: 52 mm
at 50°	: 36 mm
at 45°	: 40 mm
No-load Speed	: 3,900 rpm
Battery Voltage	: 18 V / 2.6 Ah
Weight	: 4.1 kg

Cut off Machine

GCO 2000



Capacity

Power Input	: 2,000 W
Blade Diameter	: 355 mm
Max. Cutting Capacities	
at 90°	: 120 mm
No-load Speed	: 3,500 rpm
Weight	: 15.8 kg

Slide Mitre Saw

GCM 800 S



Capacity

Power Input	: 1,400 W
Blade Size	: 216 mm
Arbour Size	: 30 mm
No-load Speed	: 5,000 rpm
Max. Mitre	: 50° L / 58° R
Cutting Capacity	: 60 x 270 mm
Weight	: 15 kg

GCM 10-S



Capacity

Power Input	: 1,800 W
Blade Size	: 254 mm
Bore Size	: 30 mm
No-load Speed	: 4,700 rpm
Max. Mitre	: 52° L / 62° R
Cutting Capacity	: 87 x 305 mm
Weight	: 21.5 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Compound Mitre Saw

GCM 10



Capacity	
Power Input	: 1,800 W
Blade Size	: 254 mm
Arbour Size	: 25.4 / 30 mm
No-load Speed	: 4,500 rpm
Max. Mitre	: 48° L / 49° R
Cutting Capacity	: 89 x 95 mm
Weight	: 15 kg

Combination Saw

GTM 12

NEW



Capacity	
Power Input	: 1,800 W
Blade Size	: 305 mm
Bore Size	: 30 mm
No-load Speed	: 4,300 rpm
Max. Mitre	: 48° L / 48° R
Cutting Capacity	: 95 x 151 mm
Weight	: 22 kg

Mitre Saw Stand

T1B

NEW



Capacity

Length of work bench	
without extension	: 1,220 mm
Length of work bench	
with extension	: 2,630 mm
Weight	: 17 kg / 22 kg

T2B

NEW



Capacity

Length of work bench	
without extension	: 2,510 mm
Weight	: 35 kg

Foam Cutter

GSG 300



Capacity	
Power Input	: 350 W
Cutting Capacity	: 300 mm
No-load Stroke Rate	: 3,200 spm
Weight	: 1.6 kg

Planer

GHO 10-82



Capacity	
Power Input	: 710 W
Planing Width	: 82 mm
Planing Depth	: 0-3.0 mm
No-load Speed	: 16,500 rpm
Weight	: 2.5 kg

Orbital Sander

GSS 230



Capacity	
Power Input	: 190 W
Orbit Rate	: 24,000 opm
Sanding Plate	: 92 x 182 mm
Weight	: 1.4 kg

GSS 280 A



Capacity	
Power Input	: 330 W
Orbit Rate	: 22,000 opm
Sand Paper Size	: 115 x 280 mm
Clamping Velcro	: 115 x 230 mm
Base Size	: 115 x 230 mm
Weight	: 2.6 kg

Eccentric Sander

GEX 125-1 AE



Capacity	
Power Input	: 250 W
No-load Speed	: 7,500-12,000 rpm
Oscillating Circuit	
Diameter	: 2.5 mm
Orbit Rate	: 15,000-24,000 opm
Sanding Plate	: 125 mm
Weight	: 1.3 kg

Belt Sander

GBS 75 A



Capacity	
Power Input	: 710 W
No-load Belt Speed	: 300 m/min
Sanding Surface	: 75 x 130 mm
Belt Size	: 75 x 533 mm
Weight	: 3.2 kg

GBS 100 A



Capacity	
Power Input	: 1,200 W
Sanding Width	: 100 mm
Belt Length	: 610 / 620 mm
Belt Speed	: 450 m / min
Weight	: 6.2 kg

Blower

GBL 800 E



Capacity	
Power Input	: 800 W
No-load Speed	: 16,000 rpm
Air Volume	: 4.5 m³/min
Weight	: 1.8 kg

Mini Router/Trimmer

GMR 1



Capacity	
Power Input	: 550 W
Collet	: 6 mm or 1/4"
No-load Speed	: 33,000 rpm
Weight	: 1.5 kg

Hot Air Gun

GHG 600-3



Capacity	
Power Input	: 1,800 W
Temperature	: 50 / 400 / 600°C
Air Flow	: 250 / 350 / 500 l/min
Weight	: 0.8 kg

GHG 630 DCE



Capacity	
Power Input	: 2,000 W
Temperature	: 50-630°C
Air Flow	: 150 / 300 / 500 l/min
Weight	: 0.9 kg

Glue Gun

GKP 200 CE



Capacity	
Gluing Capacity	: 30 g/min
No. of Heating Elements	: 2
Warming Up Time	: 4 min
Glue Stick Length	: 200 mm
Weight	: 0.4 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Wet & Dry Vacuum Cleaner

GAS 11-21



Capacity	
Power Input	: 1,100 W
Container Volume	: 21 litre
Air Flow Max.	: 50 l/sec
Volume	: 150 mbar
Hose Diameter	: 35 mm
Weight	: 6.3 kg

Chainsaw

AKE 40-19 S



Capacity	
Power Input	: 1,900 W
Blade Length	: 400 mm
Idling Cutting Speed	: 12 m/ sec
Weight	: 4.5 kg

Cordless Grass Shear

ISIO



Capacity	
Battery Voltage	: 3.6 V
Blade Length	: 80 mm
Weight	: 0.5 kg

Cordless Secateur

CISO



Capacity	
Battery Voltage	: 3.6 V
Max. Cutting Capacity	: 14 mm diameter
Cutting System	: Bypass
Weight	: 0.6 kg

Grass Trimmer

ART 23 EASYTRIM



Capacity	
Motor Power	: 280 W
Cutting Diameter	: 230 mm
Line Feed	: "Pro-Tap"
Line Thickness	: 1.6 mm x 8 m
Line Capacity	: 8 m
Cable Length	: 10 m
Weight	: 1.6 kg

ART 23 COMBITRIM



Capacity	
Motor Power	: 400 W
Cutting Diameter	: 230 mm
Line Feed	: "Pro-Tap"
Line Thickness	: 1.6 mm X 8 m
Extra Line	: Diameter 2.4 mm
Line Capacity	: 8 m
Weight	: 2.7 kg

Hand Mower

AHM 30



Capacity	
Width of Cut	: 30 cm
Height of Cut	: 12 - 40 mm
Cutting Adjustment	: Variable
Cylinder Blader	: 4
Weight	: 6.4 kg

Cylinder Mower

ASM 32



Capacity	
Motor Output	: 360 W
Width of Cut	: 32 cm
Height of Cut	: 12 - 32 mm
Cutting Height Adjustment	: 5 Stages
Grass Collecting Box	: 31 L
Weight	: 11 kg

Rotary Lawn Mower

ROTAK 320



Capacity	
Motor Output	: 1,000 W
Width of Cut	: 32 cm
Height of Cut	: 32 - 60 mm (3 Settings)
Grass Collecting Box	: 28 L
Weight	: 7 kg

ROTAK 34



Capacity	
Motor Output	: 1,300 W
Width of Cut	: 34 cm
Height of Cut	: 20 - 70 mm
Grass Collecting Box	: 40 L
Weight	: 11 kg

Cordless Rotary Lawn Mower


ROTAK 37 Li



Capacity	
Battery Voltage	: 36 V
Width of Cut	: 37 cm
Height of Cut	: 20 - 70 mm
Grass Collection Box	: 40 L
Weight	: 13 kg

Hedge-Cutter

AHS 480-24 T



Capacity	
Motor Output	: 550 W
Cut Length	: 480 mm
Blade Spacing	: 24 mm
Stroke Rate	: 2,800 rpm
Weight	: 3.9 kg

High Pressure Cleaner

AQUATAK ECO



Capacity	
Motor Power	: 1,450 W
Max. Pressure	: 100 bar
Max. Flow Volume	: 340 l/h
Max. Flow Temp.	: 40°C
Weight	: 6 kg

AQUATAK 1200 PLUS



Capacity	
Motor Power	: 1,750 W
Max. Pressure	: 120 bar
Max. Flow Volume	: 390 l/h
Max. Flow Temp.	: 60°C
Weight	: 13 kg

AQUATAK 1500 X



Capacity	
Motor Power	: 2,700 W
Max. Pressure	: 150 bar
Max. Flow Volume	: 530 l/h
Max. Flow Temp.	: 60°C
Weight	: 19 kg

AQUATAK 160 PRO X



Capacity	
Motor Power	: 2,800 W
Max. Pressure	: 155 bar
Max. Flow Volume	: 570 l/h
Max. Flow Temp.	: 60°C
Weight	: 29.1 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg

BOSCH POWER TOOLS

Laser Rangefinder

DLE 40

NEW



Capacity

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Measuring Range	: 0.05 - 40m
Measuring Accuracy	: ± 1.5
Measuring Units	: m/cm, ft/inches
Batteries	: 4 x 1.5 V LR03 (AAA)
Weight	: 175 g

DLE 70

NEW



Capacity

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Measuring Range	: 0.05 - 70 m
Measuring Accuracy	: ± 1.5
Measuring Units	: m/cm, ft/inches
Batteries	: 4 x 1.5 V LR03 (AAA)
Weight	: 180 g

DLE 150



Capacity

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Measuring Range	: 0.30 - 150 m
Measuring Accuracy	: ± 2
Measuring Units	: m/cm, ft/inches
Batteries	: 4 x 1.5 V LR06 (AA)
Weight	: 400 g

All-Purpose Detector

DMF 10 ZOOM



Capacity

Max. Measuring Depth	
Ferrous Metals	: 100 mm
Non-Ferrous Metals	: 80 mm
Accuracy	: ± 5 mm
Copper Conductors	: 50 mm
Wood	: 20 mm
Weight	: 240 g

D-TECT 100



Capacity

Max. Measuring Depth	: 100 mm
Accuracy	: ± 5 mm
Power Supply	: 4 x 1.5 V LR6 (AA)
Detectable Materials	: Plastic pipes, cables of all kinds, ferrous / non-ferrous metals, wood, cavities.
Weight	: 0.8 kg

Line Laser

GLL 2-50

NEW



Capacity

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Working Range	: 20 m
Working Range With Receiver	: 50 m
Leveling Accuracy	: ± 0.3 mm / m
Batteries	: 3 x 1.5 V LR6 (AA)
Weight	: 0.45 kg

Laser Level

GTL 3

NEW



Capacity

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Accuracy	: ± 0.2 mm / m
Accuracy between 45° and 90° -Line	: ± 0.4 mm / m
Batteries	: 4 x 1.5 V LR6 (AA)
Weight	: 0.5 kg

Point Laser

GPL 5

NEW



Capacity

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Working Range	: 30 m
Self-leveling Range	: $\pm 3^\circ$ / $\pm 5^\circ$
Leveling Accuracy	: ± 0.3 mm
Batteries	: 3 x 1.5 V LR6 (AA)
Weight	: 0.25 kg

Rotation Laser Level

GRL 150 HV

NEW



Capacity

Laser Diode	: 635 nm, < 5mW
Laser Class	: 2
Working Range	: 30 m
Working Range With Receiver	: 150 m
Leveling Accuracy	: ± 0.1 mm / m
Batteries	: 4 x 1.5 V LR20 (D)
Weight	: 1.8 kg

Digital Spirit Level

DWM 40 L



Capacity

Measurement Range	: 0 - 220°
Electronics Measurement	
Accuracy, Angles	: $\pm 0.1^\circ = \pm 1.8$ mm/m
Electronics Measurement	
Accuracy, Vials	: $\pm 0.05^\circ = \pm 1$ mm/m
Power supply	: 4 x 1.5 V LR6 (AA)
Weight	: 1.1 kg

Digital Inclinometer

DNM 60 L

NEW



Capacity

Length	: 600 mm
Measuring Range	: 360° (4° x 90°)
Measuring Accuracy	: electronic at 0°/90°: $\pm 0.05^\circ$
Battery Performance	: approx 200 h
Weight	: 0.7 kg

DNM 120 L



Capacity

Length	: 1200 mm
Measuring Range	: 360° (4° x 90°)
Measuring Accuracy	: Electronic at 0°/90°: $\pm 0.05^\circ$
Display of measurements results	: $\pm 0.1^\circ$ or mm/m
Automatic deactivation	: approx. 5 min
Power supply	: 1 x 9 V 6LR61
Weight	: 1.3 kg



友益 (新) 私人有限公司

YEW AIK (S) PRIVATE LIMITED

No. 101 KITCHENER ROAD, #01-15 & 17 (MAUDE ROAD),
JALAN BESAR PLAZA, SINGAPORE 208511

TEL: (65) 6296 3731 / 6296 2026 / 6294 3212 / 6296 1956 FAX: (65) 6298 0472

EMAIL: sales@yewaik.com.sg WEBSITE: www.yewaik.com.sg